


Three-phase spotlight
Brazo, 9.9 W, 6,000 K, silver



Housing Material	Aluminium	Height	100 mm
Housing Color	Silver	Product weight	440 g
Mounting Type	Top mounting	Working Temperature	-5 to 40 °C
Mounting Location	Inside	Storage Temperature	-10 to 60 °C
Mounting Area	Ceiling installation	IP Protection Class	IP 20
Functions	Phase switch		
Protection Class	Protection class I/ protective grounding	Life Time L70 / B50	25000 h
Rated Input	9.9 W	Switching Cycles	100000
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz	Power Consumption	10 kWh/1000h
Power Supply Unit incl.	Yes	EEI	G
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Lightcolor	Cold white (CW)		
Color Temperature	6000 K		
Colour Consistency	6 SDCM		
Colour consistency light source	6 SDCM		
CRI (Ra)	80		
Rated Luminous Flux	480 lm		
Luminous Efficiency	48.5 lm/W		
Rated Angle of Reflection	20 Degree		
Light Distribution	Symmetric		
Distribution Characteristic 120°	DLS		
Swivel Angle	180 Degree		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Length	60 mm		
Width	90 mm		

