


Strip light**Professional, COB, 24 V-15 W, 3000 K, IP20, 5 m**

Housing Color	White	LED Distance	3.47 mm
Mounting Location	Inside		
Protection Class	Protection class III/safety extra-low voltage	Bending Radius min.	30 mm
Operating Mode	Constant voltage	Total Length to be Operated max.	5 m
Rated Input 1m	15 W	Length	5000 mm
Rated Power Consumption Standby	0.5 W	Width	10 mm
Rated Input Voltage	24 V/DC	Height	2.2 mm
Power Supply Unit incl.	No	Product weight	70 g
Connection Cable Primary	Yes	Working Temperature	-20 to 50 °C
Primary Connection	With free strand / conductor ends	Storage Temperature	-30 to 80 °C
Primary Cable Length	0.5 m	IP Protection Class	IP 20
Connection Cable Secondary	Yes	Life Time L70 / B50	54000 h
Secondary Connection	Open cables	Life Time L80 / B10	54000 h
Secondary Cable Length	0.5 m	Switching Cycles	27000
Dimmable	Yes	Power Consumption	15 kWh/1000h
Control	Dimmable via optional controller	EEL	C
Number of Channels	1		
Light Source	LED, Light source not changeable		
Lightcolor	Warm white (WW)		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour consistency light source	6 SDCM		
CRI (Ra)	90		
Rated Angle of Reflection	180 Degree		
Luminous Flux 1m	2550 lm		
Luminous Efficiency 1m	170 lm/W		
LED/Meter	288		
Segment Length	27.77 mm		
Segment LED Quantity	8		

