



PRO OFFICE SANO series ceiling lights are an efficient solution for renovating and modernising old T5/T8 louver lights. Due to slightly larger dimensions, the lights cover the old installations and so do not require the ceiling to be repainted.

Arrestor cables, plug connectors and mounting brackets make installation so easy that it can be performed by one person. In addition to ease of installation, the series offers impressive technical highlights: It provides flexible light control via CCT switch (3,000 K/4,000 K), dimmable variants (leading-edge/trailing-edge or DALI) and output adjustment in four stages (TRIAC variants only). They are also eligible for BEG German federal

Special features

- Renovation solution for T5/T8 louver lights
- uniform illumination
- Covers the old installation, therefore no repainting necessary
- Easy to install due to plug connector, arrestor cables and mounting bracket
- Light colour adjustable in three levels
- Output adjustable in four levels [TRIAC variants only]
- Microprismatic surface structure
- Eligible for BEG German federal funding for energy-efficient buil-

Housing Material	Aluminium, Stainless steel	Light direction	Below
Housing Color	White	Length	625 mm
Halogen free	Yes	Width	625 mm
Functions	Emergency power capable, Corridor function DALI	Height	48 mm
Protection Class	Protection class I/ protective grounding	Working Temperature	-10 to 40 °C
Rated Input	35 W	Storage Temperature	-10 to 40 °C
Rated Power Consumption Standby	0.5 W	IP Protection Class	IP 40
Rated Power Consumption Network Standby	0.5 W	Life Time L80 / B20	50000 h
Rated Input Voltage Frequency	198-264 V/AC 50 / 60 Hz	Switching Cycles	100000
Power Supply Unit incl.	Yes	EEI	F
Dimmable	Yes		
Control	DALI 2 / DT6, Intelli Push-Dim		
Motion Detector	No		
Voltage range DC	176-280 V/DC		
Voltage range emergency lighting	176-280 V/DC		
EOFI	100 %		
Light Source	LED, Light source not changeable		
Color Temperature	3000/3500/4000 K		
Colour Consistency	3 SDCM		
Colour consistency light source	3 SDCM		
CRI (Ra)	90		
Rated Luminous Flux	4400/4700/4600 lm		
Rated Angle of Reflection	90 Degree		
UGR	19		
Light Exit Surfaces	1 PCS		
Light characteristics	Direct		

