

Strip light
Standard, COB, 24 V-15 W, 2700-6500 K, IP20, 5 m



Housing Color	White
Mounting Location	Inside
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant voltage
Rated Input 1m	15 W
Rated Power Consumption Standby	0.5 W
Rated Input Voltage	24 V/DC
Power Supply Unit incl.	No
Connection Cable Primary	Yes
Primary Connection	With free strand / conductor ends
Primary Cable Length	0.5 m
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Secondary Cable Length	0.5 m
Dimmable	Yes
Control	Dimmable via optional controller
Number of Channels	2
Light Source	LED, Light source not changeable
Lightcolor	Warm white/cold white
Colour Temperature	2700-6500 K
Colour Consistency	5 SDCM
Colour consistency light source	5 SDCM
CRI (Ra)	90
Rated Angle of Reflection	180 Degree
Luminous Flux 1m	1550 lm
Segment Length	27.8 mm
LED Distance	1.73 mm
Bending Radius min.	15 mm

Total Length to be Operated max.	5 m
Length	5000 mm
Width	10 mm
Height	1.8 mm
Product weight	114 g
Working Temperature	-20 to 50 °C
Storage Temperature	-25 to 60 °C
IP Protection Class	IP 20
Life Time L70 / B50	54000 h
Life Time L80 / B10	47000 h
Switching Cycles	30000 PCS
Power Consumption	15 kWh/1000h
EEI	F

