


Surface-mounted wall light

Shoreline Pro Round Up+Down, 20 W, DIM, 3000/4000 K, light grey



Special features

- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Housing Material	Aluminium
Housing Color	Light grey
Material of Lens	Glass
Colour of Lens	Clear
Surface Structure of Lens	Clear
Through Wiring possible	Yes
Mounting Type	Top mounting
Mounting Location	Outside
Mounting Area	Wall installation
Ultraviolet resistance	Yes
Functions	Seawater resistant
Protection Class	Protection class I/ protective grounding
Rated Input	20 W
Rated Power Consumption Standby	0.5 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Number of Cable Entries	2 PCS
Dimmable	Yes
Control	Trailing-edge dimmer
Motion Detector	No

Light Source	LED, Light source changeable TC
Color Temperature	3000/4000 K
Colour Consistency	4 SDCM
Colour consistency light source	3 SDCM
CRI (Ra)	92
Rated Luminous Flux	1700/1900 lm
Rated Angle of Reflection	36 Degree
UGR	19

Light Exit Surfaces	2
Light characteristics	Direct, Indirect

Light direction	Top, Below
Height	238 mm
Diameter	100 mm
Base length	40 mm
Base L x W x H	40 x 80 x 130 mm
Base width	80 mm
Base height	130 mm
Working Temperature	-20 to 45 °C
Storage Temperature	-20 to 60 °C
Surface Temperature max.	43.5 °C
IP Protection Class	IP 65
IK Protection Class	IK08
Inrush Current max.	10 A / 32 µs
Max. units per MCB B10	67
Max. units per MCB B16	107
Max. units per MCB C10	107
Max. units per MCB C16	171

Life Time L70 / B50	50000 h
Switching Cycles	
Power Consumption	
Energy Efficiency Class Lightsource	

