




The ALKES series is not a traditional wall-mounted light, but, with its SMD-LED panel, has floodlight similarities. The highlight: the upper housing part is tilted forwards 45° from the façade to direct the warm white light in a targeted manner onto the surface to be illuminated. In addition, the ALKES also looks great when switched off with its modern design and rounded edges.

Special features

- high luminous efficacy
- homogeneous light distribution

Housing Material	Aluminium
Housing Color	Dark grey
Material of Lens	Glass
Mounting Type	Top mounting
Mounting Location	Outside
Mounting Area	Wall installation
Ultraviolet resistance	Yes
Protection Class	Protection class I/ protective grounding
Rated Input	21 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Dimmable	No
Motion Detector	No

Working Temperature	-20 to 50 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 65
Max. units per MCB B10	40 PCS
Max. units per MCB B16	64 PCS
Max. units per MCB C10	64 PCS
Max. units per MCB C16	102 PCS

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour consistency light source	6 SDCM
CRI (Ra)	80
Rated Luminous Flux	920 lm
Luminous Efficiency	43.8 lm/W
Rated Angle of Reflection	110 Degree
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Length	200 mm
Width	126 mm
Height	184 mm

