Art.-Nr. 348072

Surface-mounted ceiling and wall lights
Mensae round Motion, 20 W, 3,000 K, dark grey

DEKOLIGHT

IK08 IP65 UGR<10



Versatile and functional - The Mensae LED outside wall and ceiling light boasts an impressive flat design and can be used both indoors and outdoors with its movement sensor including daylight sensor. The white cover atop the dark grey aluminium die-cast frame houses 96 warm white LEDs with 18 watts and 3,000 K.

Special features

- Corridor function
- Adjustable motion detector [hold time / detection area]
- Daylight sensor

Housing Material	Aluminium
Housing Color	Dark grey
Material of Lens	Polycarbonate - PC
Through Wiring possible	Yes
Mounting Type	Top mounting
Mounting Location	Outside
Mounting Area	Ceiling installation
Protection Class	Protection class I/ protective grounding
Rated Input	16 W
Rated Power Consumption Standby	0.3 W
Rated Power Consumption Network Standby	0.5 W
Rated Input Voltage Frequency	100-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Dimmable	No
Motion Detector	Yes
Kind of Motion Detector	High frequency
Detection Distance	9-12 m
Angle of Detection	120 Degree
Motion detector changeable	Yes
Adjustable brightness threshold	Yes
Brightness threshold	150-1500 lx
Adjustable follow-up time	Yes
Follow-up time	1-3 min
Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour consistency light source	6 SDCM
CRI (Ra)	80
Rated Luminous Flux	1500 lm
Luminous Efficiency	67 lm/W

Rated Angle of Reflection	110 Degree
UGR	10
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Top, Below, Side
Height	54 mm
Diameter	300 mm
Base height	28.5 mm
Base H x Ø	28.5 x 170 mm
Base diameter	170 mm
Working Temperature	-25 to 45 °C
Storage Temperature	-30 to 55 °C
IP Protection Class	IP 65
IK Protection Class	IK08
Max. units per MCB B10	110 PCS
Max. units per MCB B16	170 PCS
Max. units per MCB C10	130 PCS
Max. units per MCB C16	210 PCS
Life Time L70 / B50	
Life Time L80 / B10	
Life Time L80 / B50	
Switching Cycles	
Power Consumption	
Energy Efficiency Class Lightsource	



IP65

Deko-Light Elektronik-Vertriebs GmbH
Auf der Hub 2 | D-76307 Karlsbad
www.deko-light.com
deko@deko-light.com