


Surface-mounted wall light
Shoreline Pro Round, 20 W, DIM, 3000/4000 K, dark grey

Special features


- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Housing Material	Aluminium
Housing Color	Dark grey
Material of Lens	Glass
Colour of Lens	Clear
Surface Structure of Lens	Clear
Through Wiring possible	Yes
Mounting Type	Top mounting
Mounting Location	Outside
Mounting Area	Wall installation
Ultraviolet resistance	Yes
Functions	Nightsaver, Seawater resistant
Protection Class	Protection class II / protective grounding
Rated Input	20 W
Rated Power Consumption Standby	0.5 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Number of Cable Entries	2 PCS
Dimmable	Yes
Control	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No
Voltage range DC	176-250 V/DC
Light Source	LED, Light source changeable TC
Color Temperature	3000/4000 K
Colour Consistency	4 SDCM
Colour consistency light source	3 SDCM
CRI (Ra)	92
Rated Luminous Flux	2000/2200 lm
Rated Angle of Reflection	36 Degree
UGR	16

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below
Height	218 mm
Diameter	140 mm
Base length	40 mm
Base L x W x H	40 x 80 x 130 mm
Base width	80 mm
Base height	130 mm

Working Temperature	-20 to 45 °C
Storage Temperature	-20 to 45 °C
Surface Temperature max.	38 °C
IP Protection Class	IP 65
IK Protection Class	IK08
Inrush Current max.	5 A / 100 µs
Max. units per MCB B10	71
Max. units per MCB B16	114
Max. units per MCB C10	71
Max. units per MCB C16	

Life Time L70 / B50	50000h
Switching Cycles	100000
Power Consumption	20W
Energy Efficiency Class Lightsource	A



00h
 ct contains a
 of energy
 lass E.

