


Power supply unit (CC, DC) dimmable
QUICK, CC, 1,050 mA, 25-40 V, 42 W

Special features

- Particularly quick and easy to install with integrated three-pin feed-through wiring
- Push terminals for wires from 0.5 to 1.5 mm²
- Push terminals also on secondary side
- No additional installation material required
- Can be dimmed using compatible [C-compatible] trailing-edge phase dimmers
- Flicker-free
- Secured against short circuits and overloads

Housing Material	Plastic
Housing Color	Black
Functions	Short-circuit proof, Lamp control gear 110, Furniture installation, Protective extra-low voltage, Overloading protection, Overtemperature protection

Operating Mode	Constant current
Protection Class	Protection class II/protective insulation
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power	23.1-44.1 W
Output Voltage	22-42 V/DC
Output Current	1050 mA
Dimmable	Yes
Control	Trailing-edge dimmer
Number of Channels	1
Power Factor	0.98

Max. units per MCB B10	35
Max. units per MCB B16	57
Max. units per MCB C10	35
Max. units per MCB C16	57
Inrush Current max.	5 A / 100 µs
Reference Point T_c	80 °C
Working Temperature	-20 to 45 °C
Storage Temperature	-20 to 70 °C
IP Protection Class	IP 20

Life Time	50000 h
------------------	---------

Length	208 mm
Width	60 mm
Height	32 mm
Product weight	224 g

