


Surface-mounted ceiling light

Lautaro 900/100 Prism, 60 W, DALI, 2700 K, white



Housing Material	Aluminium, Steel
Housing Color	White
Material of Lens	Polycarbonate - PC
Surface Structure of Lens	Microprismatic
Through Wiring possible	Yes
Mounting Type	Top mounting
Mounting Location	Inside
Mounting Area	Ceiling installation
Protection Class	Protection class I/ protective grounding
Rated Input	60 W
Rated Power Consumption Standby	0.3 W
Rated Input Voltage Frequency	198-264 V/AC 50 / 60 Hz
Dimmable	Yes
Control	DALI 2 / DT6, Push-Dim
Voltage range DC	176-276 V/DC

Light Source	LED, Light source changeable TC
Color Temperature	2700 K
Colour Consistency	3 SDCM
Colour consistency light source	2 SDCM
CRI (Ra)	90
Rated Luminous Flux	7400 lm
Luminous Efficiency	123 lm/W
Rated Angle of Reflection	90 Degree
UGR	19


Light Exit Surfaces	1 PCS
Light characteristics	Direct
Light direction	Below

Height	100 mm
Diameter	900 mm

Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class E.
--	--

Working Temperature	-20 to 50 °C
Storage Temperature	-40 to 80 °C
Surface Temperature max.	80 °C
IP Protection Class	IP 40
IK Protection Class	IK05
Inrush Current max.	5.1 A / 44.5 µs
Max. units per MCB B10	21 PCS
Max. units per MCB B16	34 PCS
Max. units per MCB C10	21 PCS
Max. units per MCB C16	34 PCS

Life Time L70 / B50	180000 h
Life Time L80 / B10	120000 h
Life Time L80 / B50	130000 h
Life Time L90 / B10	50000 h
Life Time L90 / B20	60000 h
Switching Cycles	100000 PCS
Power Consumption	60 kWh/1000h



Art.-Nr. 950965

Surface-mounted ceiling light
Lautaro 900/100 Prism, 60 W, DALI, 2700 K, white

