


Bollard light**Facado 2 angular tinted 1,000 mm, 1x max. 20 W, E27, dark grey**

Our FACADO series bollard lights feature IP65 degree of protection for excellent weather resistance. Choose between an opal diffuser or a transparent diffuser with smoked glass to suit your requirements. The series is available in two different sizes (650 mm/1,000 mm) and features an E27 socket for replaceable lamps. The newly designed lamp head provides even better illumination. The FACADO light is made from high-quality die-cast aluminium and available in dark grey or rust and in square or rounded designs.

The IP67 connection box features a double M20 cable gland suitable for buried cables in sizes $3 \times 1.5 \text{ mm}^2$, $5 \times 1.5 \text{ mm}^2$ or $3 \times 2.5 \text{ mm}^2$, and more.

Special features

- IP65 weather resistance
- IP67 connection box suitable for e.g. buried cables $3 \times 1.5 \text{ mm}^2/5 \times 1.5 \text{ mm}^2/3 \times 2.5 \text{ mm}^2$
- Newly designed lamp head for improved illumination
- Available with an opal diffuser or a transparent diffuser with smoked glass
- Ideal for e.g. ST64 bulbs and A60/70 bulbs

Housing Material	Aluminium, Polycarbonate
Housing Color	Dark grey
Surface structure	Matt
Material of Lens	Polycarbonate - PC
Colour of Lens	Smoke-coloured
Surface Structure of Lens	Transparent
Mounting Type	Top mounting
Mounting Location	Outside
Mounting Area	Bottom panel mounting
UV resistance	Yes

Storage Temperature	-10 to 60 °C
IP Protection Class	IP 65
IK Protection Class	IK05

Protection Class	Protection class I/ protective grounding
max. Power	1x max. 20 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Socket Description	E27
Illuminant Design	A60, A70, ST64
Socket Quantity	1 PCS
Dimmable	Yes
Control	Dimmable via optional light source
Motion Detector	No

Execution	Without lamp
------------------	--------------

Light Exit Surfaces	5
Light characteristics	Direct
Light direction	Top, Side

Length	108 mm
Width	108 mm
Height	1000 mm
Product weight	4000 g

Working Temperature	-20 to 40 °C
----------------------------	--------------

