


**Special features**

- Particularly quick and easy to install with integrated three-pin feed-through wiring
- Push terminals for wires from 0.5 to 1.5 mm²
- Push terminals also on secondary side
- No additional installation material required
- Can be dimmed using compatible [C-compatible] trailing-edge phase dimmers
- Flicker-free
- Secured against short circuits and overloads

Housing Material	Plastic
Housing Color	Black
Functions	Short-circuit proof, Lamp control gear 110, Furniture installation, Protective extra-low voltage, Overloading protection, Overtemperature protection

Operating Mode	Constant current
Protection Class	Protection class II/protective insulation
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power	40.5-63 W
Output Voltage	27-42 V/DC
Output Current	1500 mA
Dimmable	Yes
Control	Trailing-edge dimmer
Number of Channels	1
Power Factor	0.95

Max. units per MCB B10	23
Max. units per MCB B16	37
Max. units per MCB C10	25
Max. units per MCB C16	41
Inrush Current max.	30 A / 100 µs
Reference Point Tc	90 °C
Working Temperature	-20 to 45 °C
Storage Temperature	-20 to 70 °C
IP Protection Class	IP 20

Length	208 mm
Width	60 mm
Height	32 mm
Product weight	770 g

