


Strip light**Professional, COB, 24 V-15 W, 2700 K, IP20, 5 m**

Housing Color	White	LED Distance	3.47 mm
Mounting Location	Inside	Bending Radius min.	30 mm
Protection Class	Protection class III/safety extra-low voltage	Total Length to be Operated max.	5 m
Operating Mode	Constant voltage	Length	5000 mm
Rated Input 1m	15 W	Width	10 mm
Rated Power Consumption Standby	0.5 W	Height	2.2 mm
Rated Input Voltage	24 V/DC	Product weight	70 g
Power Supply Unit incl.	No	Working Temperature	-20 to 50 °C
Connection Cable Primary	Yes	Storage Temperature	-30 to 80 °C
Primary Connection	With free strand / conductor ends	IP Protection Class	IP 20
Primary Cable Length	0.5 m	Life Time L70 / B50	54000 h
Connection Cable Secondary	Yes	Life Time L80 / B10	54000 h
Secondary Connection	Open cables	Switching Cycles	27000
Secondary Cable Length	0.5 m	Power Consumption	15 kWh/1000h
Dimmable	Yes	EEL	E
Control	Dimmable via optional controller		
Number of Channels	1		
Light Source	LED, Light source not changeable		
Lightcolor	Warm white (WW)		
Color Temperature	2700 K		
Colour Consistency	6 SDCM		
Colour consistency light source	6 SDCM		
CRI (Ra)	90		
Rated Angle of Reflection	180 Degree		
Luminous Flux 1m	2100 lm		
Luminous Efficiency 1m	141 lm/W		
LED/Meter	288		
Segment Length	27.77 mm		
Segment LED Quantity	8		

