

Artikel Nr.: 872045

Netzgerät (CV, DC) dimmbar, LED Sicherheitstransformator, DIM, CV, 60VA/24V DC



IP 67 

Elektrische Daten

Betriebsart	Spannungskonstant	Eingangsspannung	220-240 V/AC 50 / 60 Hz
Leistung	12,0-60,0 W	Leistungsfaktor	
Ausgangsspannung	24 V/DC	Anschlußmöglichkeit	Offene Kabel
Ausgangsstrom	500-2500 mA		

Produkteigenschaften

 Schutzklasse II	 Überspannungsschutz
SELV Schutzkleinspannung	 Lampenbetriebsgerät 110
 Kurzschlußfest	 Möbeleinbau nicht geeignet
 Überlastschutz	ErP Standby-Stromverbrauch < 0,5 W
 Übertemperaturschutz	LVD Sicherheit nach EN 61347
 Sicherheitstrafo	EMC Funkentstörung + Störfestigkeit nach EN 55015 + EN 61547
 dimmbar - Phasenanschnittsdimmer	EMC Netzstromoberwellen + Flicker nach EN 61000-3-2 + EN 61000-3-3

Schwarze Felder sind zutreffend / graue Felder sind nicht zutreffend

Artikel Nr.: 872045

Netzgerät (CV, DC) dimmbar, LED Sicherheitstransformator, DIM, CV, 60VA/24V DC

Abmessungen und Gewicht

Grenzwerte

Länge	150,00 mm	Betriebstemperatur	-20 bis 40 °C
Breite	90,00 mm	Gehäusetemperatur	
Höhe	70,00 mm	max. Menge Sicherungsautomaten	
Durchmesser	0,00 mm	max. Einschaltstrom	
Gewicht	2100 g	kapazitive Last	

Article No.: 872045

Power supply unit (CV, DC) dimmable, LED safety transformer, DIM, CV, 60 VA/24 V DC



IP 67 

Electrical Characteristics

Operating mode	Constant voltage	Input voltage	220-240 V/AC 50 / 60 Hz
Power	12,0-60,0 W	Power factor	
Output voltage	24 V/DC	Connection possibility	Open cables
Output current	500-2500 mA		

Product features

 Protection class II	 Overvoltage protection
 Low voltage protection	 Lamp control gear 110
 Short circuit protection	 Not suitable for furniture installation
 Overload protection	 Standby-power consumption < 0,5 W
 Overheating protection	 Safety according to EN 61347
 Safety transformer	 Interference suppression + immunity according to EN 55015 + EN 61547
 dimmable - Leading-edge dimmer	 Mains harmonics + flicker according to EN 61000-3-2 + EN 61000-3-3

Black fields are applicable / gray fields are not applicable

Article No.: 872045

Power supply unit (CV, DC) dimmable, LED safety transformer, DIM, CV, 60 VA/24 V DC

Dimensions & Weight		Absolute maximum ratings	
Length	150,00 mm	Operating temperature	-20 bis 40 °C
Width	90,00 mm	Case temperature	
Height	70,00 mm	max. amount of circuit breakers	
Diameter	0,00 mm	max. inrush current	
Product weight	2100 g	capacitive load	