

Surface-mounted ceiling light
Altas Motion, 12 W, 3,000/4,000/6,000 K, white



It takes a lot to catch the Altas series off guard. Thanks to IP54 and impact strength class IK10, these slender outdoor lamps are impressive all-rounders both in commercial and private settings. Altas Motion lamps offer additional versatility with their integrated motion sensor (programmable using supplied remote control) and the adjustable light colour for different lighting scenarios.

Special features

- Light colour adjustable in three steps
- Optional surface-mounted cable entry
- Feed-through wiring possible
- Motion detector can be adjusted by remote control (in scope of delivery)

Housing Material	Plastic
Housing Color	White
Halogen free	Yes
Mounting Type	Top mounting
Mounting Location	Inside
Mounting Area	Ceiling installation
Protection Class	Protection class II/ protective insulation
Rated Input	12 W
Rated Power Consumption Network Standby	0.5 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Dimmable	No
Motion Detector	Yes
Kind of Motion Detector	High frequency
Detection Distance	1-12 m
Angle of Detection	150 Degree
Motion detector changeable	Yes
Adjustable brightness threshold	No
Adjustable follow-up time	Yes
Follow-up time	5-600 s

Light Source	LED, Light source not changeable
Color Temperature	3000/4000/6000 K
Colour Consistency	6 SDCM
Colour consistency light source	6 SDCM
CRI (Ra)	85
Rated Luminous Flux	1260/1320/1320 lm
Luminous Efficiency	105 lm/W
Rated Angle of Reflection	120 Degree
Distribution Characteristic 120°	NDLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below
Height	48 mm
Diameter	220 mm

Working Temperature	-40 to 50 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 54
IK Protection Class	IK10
Max. units per MCB B10	121 PCS
Max. units per MCB B16	121 PCS
Max. units per MCB C10	192 PCS
Max. units per MCB C16	192 PCS

Life Time L70 / B50	50000 h
Switching Cycles	75000
Power Consumption EEI	12 kWh/1000h E

