

Three-phase pendant lamp

Slim, 5 W, DIM, 2,700 K, black



Matching SLIM series pendant lamps are available for the current track system. The die-cast aluminium light body is the same size for all variants [300 × 39 mm]. The pendant lamps for current tracks allow suspended mounting up to max. 180 cm.

The single-luminaire SLIM current track lights therefore are especially well suited to gastronomy and retail projects with variable room layouts. The premium SLIM series is rounded off with a flexible fabric cable.

Special features

- Extra-soft fabric cable
- Glare-free due to low UGR value [<19]
- Suspended mounting up to 1,800 mm
- Slim design at just 39 mm in diameter

Housing Material	Aluminium
Housing Color	Black
Colour of Lens	Transparent
Surface Structure of Lens	Structured
Halogen free	No
Mounting Type	Top mounting
Mounting Location	Inside
Mounting Area	Ceiling installation
Functions	Phase switch
Protection Class	Protection class I/ protective grounding
Rated Input	5 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Dimmable	Yes
Control	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No

Light Source	LED, Light source changeable TC
Lightcolor	Warm white (WW)
Color Temperature	2700 K
Colour Consistency	6 SDCM
Colour consistency light source	6 SDCM
CRI (Ra)	90
Rated Luminous Flux	500 lm
Luminous Efficiency	100 lm/W
Rated Angle of Reflection	24 Degree
UGR	19
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
----------------------------	---

Light characteristics	Direct
Light direction	Below
Height	300 mm
Diameter	39 mm
Pendulum Length max.	1500 mm
Product weight	476 g
Working Temperature	-20 to 45 °C
Storage Temperature	-20 to 65 °C
IP Protection Class	IP 20
Max. units per MCB B10	230 PCS
Max. units per MCB B16	368 PCS
Max. units per MCB C10	230 PCS
Max. units per MCB C16	368 PCS

Life Time L70 / B50	50000 h
Switching Cycles	100000
Power Consumption	5 kWh/1000h
Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class F

