


Surface-mounted wall light
Shoreline Pro Round, 12 W, DIM, 3000/4000 K, white

Special features

- light colour adjustable in 2 stages
- through-wiring possible
- seawater-resistant
- easy and quick installation
- separable mounting plate with plug-in connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Housing Material	Aluminium
Housing Color	White
Material of Lens	Glass
Through Wiring possible	Yes
Mounting Type	Top mounting
Mounting Location	Outside
Mounting Area	Wall installation
Ultraviolet resistance	Yes
Functions	Nightsaver, Seawater resistant

Protection Class	Protection class I / protective grounding
Rated Input	12 W
Rated Power Consumption Standby	0.5 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Number of Cable Entries	2 PCS
Dimmable	Yes
Control	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No
Voltage range DC	176-250 V/DC

Light Source	LED, Light source changeable TC
Color Temperature	3000/4000 K
Colour Consistency	4 SDCM
Colour consistency light source	3 SDCM
CRI (Ra)	92
Rated Luminous Flux	900/1000 lm
Rated Angle of Reflection	36 Degree
UGR	21

Light Exit Surfaces	1
----------------------------	---

Light characteristics	Direct
Light direction	Below
Height	163 mm
Diameter	100 mm
Base length	40 mm
Base L x W x H	40 x 80 x 130 mm
Base width	80 mm
Base height	130 mm

Working Temperature	-20 to 45 °C
Storage Temperature	-20 to 45 °C
Surface Temperature max.	39.2 °C
IP Protection Class	IP 65
IK Protection Class	IK08
Inrush Current max.	5 A / 100 µs
Max. units per MCB B10	140
Max. units per MCB B16	224
Max. units per MCB C10	142
Max. units per MCB C16	228

Life Time L70 / B50
Switching Cycles
Power Consumption
Energy Efficiency Class Lightsources
