




Little helper, big effect. With the HERCULIS display lights in a high-quality aluminium housing, you can reach all corners of a display case. To do so, the lamp head with its 40° light emission angle can be freely rotated and swivelled in any direction. In addition, the intelligent cable routing and the ready-to-use system enable easy surface and recessed mounting in display cases, counters, sales areas or in living rooms.

Special features

- High performance with compact design
- Rotating and swivelling heads
- for recessed and surface mounting thanks to intelligent cable routing
- Ready-to-plug-in system

Housing Material	Aluminium	Storage Temperature	-10 to 45 °C
Housing Color	Silver	IP Protection Class	IP 20
Protection Class	Protection class III/safety extra-low voltage	Life Time L70 / B50	30000 h
Operating Mode	Constant current	Switching Cycles	50000
Rated Input	2 W	Power Consumption	2 kWh/1000h
Rated Input Voltage	6 V/DC	EEL	G
Rated Current	350 mA		
Power Supply Unit incl.	No		
Connection Cable Secondary	Yes		
Secondary Cable Length	1 m		
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	4000 K		
Colour Consistency	6 SDCM		
Colour consistency light source	6 SDCM		
CRI (Ra)	90		
Rated Luminous Flux	195 lm		
Rated Angle of Reflection	30 Degree		
Distribution Characteristic 120°	DLS		
Swivel Angle	350 Degree		
Light Exit Surfaces	2		
Light characteristics	Direct		
Light direction	Below		
Height	200 mm		
Diameter	39.2 mm		
Base height	4.5 mm		
Base diameter	39.2 mm		
Working Temperature	-10 to 45 °C		

